

### Product Description

myMEDIA 5842 Banner Tape is a double-sided tape with a white polyolefin liner for overlapping splicing and hemming of printed and unprinted banner materials and PVC coated textiles. It is an easy to use alternative to welding or sewing and provides secure splicing and hemming of PVC banners with smooth and textured surfaces. Also suitable for reinforcing eyelet loops. Due to the high thickness, the high-performance adhesive adapts very well to textured substrates and offers optimum bond adhesion, including extremely high shear and tensile strength and excellent plasticiser resistance. Suitable for indoor and outdoor applications.

### Physical Characteristics

Front material	No carrier	
Thickness / Weight	400 µm	
Colour / Finish	Transparent	
Adhesive	Modified acrylic adhesive	
Liner	Double-sided polyolefin liner, white	
Durability	Indoor and outdoor	
Application temperature	>= +10°C	
Temperature range	-40°C to +130°C	
Adhesion	25 N/25 mm (after 24 hours)	AFERA 5001

### Storage

Shelf life	Up to 1 year if stored in original packaging
Storage conditions	+18°C to +25°C at 50 - 60% relative humidity

### Advantages and features

- Easy to use alternative to welding or sewing
- Easier application
- Extraordinary high adhesive strength
- Extremely high tensile strength
- Excellent plasticiser resistance
- Suitable for indoor and outdoor use
- Good resistance to moisture and ageing

### Applications

- Splicing and hemming of PVC banners with smooth and structured surfaces
- Bonding of PVC-coated textiles

### Important Notice

Information on physical and chemical characteristics is based upon tests, practical knowledge and experience. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Because of the variety of uses and applications, the purchasers should independently determine, prior to use, the suitability of this material to their specific use and carefully consider the suitability and performance of the product. The purchaser shall assume all risks for any use and application of the material. All specifications and technical data are subject to change without prior notice, errors and omissions expected. All warranty matters are regulated by our general terms and conditions.