

**Product Description**

myMEDIA 6002 Photo Paper Satin is a specially coated PE photo paper developed for use on printers with Latex, Eco-Solvent, Solvent and UV-curable inks. This photo paper impresses with instant drying, very wide colour range, highest image quality, realistic photo reproduction, good tear resistance and excellent flatness. The optimal printing medium when high photo quality with high colour saturation and best detail reproduction is required.

**Physical Characteristics**

Front material	PE-coated photo paper on both sides
Thickness / Weight	230 g/m <sup>2</sup>
Colour / Finish	White, satin
Opacity	> 90%
Whiteness (CIE)	> 145
Durability	Indoor
Print side	Outside rolled

**Printing Method**

Compatible inks	HP Latex, Eco-Solvent, Solvent, UV-curable
Drying	The digital print must be ABSOLUTELY DRY prior the lamination! We recommend to dry for at least 48 hours prior to further processing in unwounded condition. If this is not possible the roll should be dried loosely winded in upright position on an air permeable (grid) floor to ensure air circulation. Insufficient drying may result in curling, shrinkage and insufficient adhesion which excludes any warranty. Therefore the drying has to be checked with practical methods like Tesatest (optimal with cross section), grab test, abrasion test and/or smell test prior to further processing and application.

**Processing and converting**

Processing	myMEDIA 6002 Photo Paper Satin dries quickly and is excellent for further processing and laminating. However, the drying time also depends on the amount of ink used. When printing from roll to roll, the printed web should be unrolled as quickly as possible and laid out flat so that the ink can completely outgas. To avoid fingerprints, we recommend the use of cotton gloves.
Notice	As paper is a natural product, there may be some variations. Basically, it should be noted that coated inkjet papers should not be compared with poster papers used in other printing processes. They have different adhesive properties due to their finish. In the interest of optimal mounting, please be sure to point out the properties and processing instructions of this product to the mounting personnel!

**Storage**

Shelf life	Up to 2 years if stored in original packaging
Storage conditions	+15°C to +25°C at 50% relative humidity

### Advantages and features

- Excellent print quality
- Very wide colour range
- Outstanding flatness
- Good price/performance ratio
- Superb opacity
- Great ink bonding

### Applications

- Photo reproductions
- Photorealistic prints
- High quality posters
- Advertising in shops
- Indoor signs and displays

### Important Notice

Information on physical and chemical characteristics is based upon tests, practical knowledge and experience. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Because of the variety of uses and applications, the purchasers should independently determine, prior to use, the suitability of this material to their specific use and carefully consider the suitability and performance of the product. The purchaser shall assume all risks for any use and application of the material. All specifications and technical data are subject to change without prior notice, errors and omissions expected. All warranty matters are regulated by our general terms and conditions.